

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	Knauf Insulation
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-KIN-20150171-CBB2-EN
ECO EPD Ref. No.	ECO-00000197
Issue date	13.07.2015
Valid to	12.07.2020

Glass Mineral Wool 036-037-038 unfaced rolls

Classic 037, Expert IPR 037, KI Fit 037, Naturoff 037, Decibel, TI 140T, TI 140W, Ultracoustic R, Unifit 037, TP 115 with **ECOSE® Technology**

Knauf Insulation

www.bau-umwelt.com / <https://epd-online.com>



General Information

Knauf Insulation

Programme holder

IBU - Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Declaration number

EPD-KIN-20150171-CBB2-EN

This Declaration is based on the Product Category Rules:

Mineral insulating materials, 07.2014
(PCR tested and approved by the SVR)

Issue date

13.07.2015

Valid to

12.07.2020



Prof. Dr.-Ing. Horst J. Bossenmayer
(President of Institut Bauen und Umwelt e.V.)



Dr. Burkhard Lehmann
(Managing Director IBU)

GMW 036-037-038 unfaced rolls with ECOSE

Owner of the Declaration

Knauf Insulation
rue E. Franqui, 7
1435 Mont-Saint-Guibert
Belgium

Declared product / Declared unit

1 m³ of GMW 036-037-038 rolls

Scope:


GMW (Glass Mineral Wool) 036-037-038 rolls are unfaced insulation products. They comply with the requirements of /EN 13162/. The thickness is ranging from 40 mm to 300 mm. The manufacturing company is Knauf Insulation - plants Krupka (Czech Republic), Lannemezan (France) and Visé (Belgium). Indicators are calculated using 2013 data. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Verification

The CEN Norm /EN 15804/ serves as the core PCR

Independent verification of the declaration
according to /ISO 14025/

internally externally



Matthias Schulz
(Independent verifier appointed by SVR)

Product

Product description

Knauf Insulation manufactures glass mineral wool insulation products such as Classic 037, Expert IPR 037, KI Fit 037, Naturoll 037, Decibel, TI 140T, TI 140W, Ultracoustic R, Unifit 037, TP115 with ECOSE® Technology. They are available in the form of slabs or rolls, and also boards. The density for glass mineral wool ranges from 10 to 85 kg/m³. In general, glass mineral wool consists of >= 92.5% inert material. The inert part is made of recycled glass (external cullet, up to 80% of the composition) and mainly sand and dolomite.

The remaining <= 7.5% are made of bio-based binder components. At Knauf Insulation, the binder used for the GMW products is the ECOSE binder whose origin is plant starch.

GMW 036-037-038 unfaced rolls are products used for their thermal, acoustical and fire characteristics. A representative product out of a particular group of products was selected for the calculation.

For the placing on the market of construction products in the European Union and EFTA (with the exception of Switzerland) /Regulation (EU) No 305/2011/ applies. The products need a Declaration of performance (DoP) taking into consideration the harmonized product

standard /EN 13162/ and the CE-mark /Regulation (EC) No 765/2008/.

Application

Main applications for GMW 036-037-038 unfaced roll are in pitched roofs, partition walls and timber frames. For the applications and use national regulations apply, in Germany the /Allgemeine bauaufsichtliche Zulassung Z-23.15-1461/ (building inspection approval) issued by the Deutsches Institut für Bautechnik (DIBt), Berlin.

Technical Data

GMW 036-037-038 unfaced rolls and their technical characteristics meet a number of technical requirements. The most important ones are summarized in the table below, which also includes references to testing methods.

Technical characteristics

Name	Value	Unit
Water vapour diffusion resistance factor /EN 13162/	1	-
Gross density /EN 1602/	14 - 18	kg/m ³
Longit. air-diffusion resist. /EN 29053/	not	kNs/m ⁴

	relevant	
Water absorption Wp /EN 1609/	< 1	kg/m ²
Water absorption Wip /EN 12087/	< 3	kg/m ²
Reaction to fire /EN 13501-1/	A1	-
Specific heat capacity /EN ISO 10456/	850	J/kgK
Acoustic absorption	not relevant	
Compression strength/resistance	not relevant	
Thermal conductivity /EN 12667/	0.036-0.037-0.038	W(mK)

well as for fire prevention in construction and industry. Raw materials used in the production of GMW are sand, limestone, soda ash and a high level of recycled glass (up to 80%). A bio-based binder, ECOSE, is spread on the fibers which polymerisation contributes to fix the product dimensions. The cured binder bonds the fibres together thus providing the necessary mat stability and mechanical strength.

Reference service life

The RSL or durability of GMW 036-037-038 unfaced rolls is as long as the lifetime of the building in which it is used.

Base materials / Ancillary materials

GMW is an insulation material of mostly inorganic origin intended for thermal and acoustic insulation, as

LCA: Calculation rules

Declared Unit

The declared unit is 1 m³ of glass mineral wool. The density used for the calculation of the LCA is 16 kg/m³.

Declared unit

Name	Value	Unit
Declared unit	1	m ³
Gross density	16	kg/m ³
Conversion factor to 1 kg	0.0625	-

System boundary

The system boundary of the EPD follows the modular approach defined by /EN 15804/.

The type of EPD is cradle-to-gate-with options.

List and explanation of the modules declared in the EPD.

The product stage (A1-A3) includes:

- A1 - raw material extraction and processing, processing of secondary material input (e.g. recycling processes),
- A2 - transport to the manufacturer and
- A3 - manufacturing.

This includes provision of all materials, products and energy, packaging processing and their transport, as well as waste processing up to the end-of waste state or disposal of final residues during the product stage. The LCA results are given in an aggregated form for the product stage, meaning that the modules A1, A2 and A3 are considered as **a unique module A1-A3**.

The construction process stage includes:

- A4 - transport to the construction site and
- A5 - installation into the building.

The transport to the building site (A4) is included in the LCA calculation. For GMW 036-037-038 unfaced rolls, the average transport distance is assumed to be 600 km with a truck capacity utilization of 70%.

Module A5 has neither been included nor declared in this EPD, since it depends on the application, and method or tools used which can be very diverse, as GMW 036-037-038 unfaced rolls are used in different applications. Therefore, the treatment of the packaging waste after the installation of the product has not been considered.

The use stage.

Because they are specific for the building, its use and location, none of the modules related to building maintenance and operation (B1 to B7) have been taken into account in this EPD.

The end-of-life stage includes:

- C1 - de-construction, demolition,
- C2 - transport to waste processing,
- C3 - waste processing for reuse, recovery and/or recycling and
- C4 - disposal.

This includes provision of all transports, materials, products and related energy and water use, but only modules C2 and C4 are reported, as they are considered the most relevant scenarios for glass mineral wool products.

Although glass mineral wool products from Knauf Insulation are partly recycled at their end-of-life, there is not yet an established collection system and as such the assumption chosen in this study, 100% landfilled after the use phase, is the most conservative approach.

Module D includes re-use, recovery and/or recycling potentials.

According to /EN 15804/, any declared benefits and loads from net flows leaving the product system not allocated as co-products and having passed the end-of waste state shall be included in module D.

No benefits and loads are considered so module D is not included in the background model.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The following technical information can be used for the development of specific scenarios in the context of a building assessment.

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel	0.0025	l/100km
Transport distance	600	km
Capacity utilisation (including empty runs)	70	%
Gross density of products transported	16	kg/m ³

Reference service life

Name	Value	Unit
Reference service life	50	a

End-of-life (C1 - C4)

Name	Value	Unit
Landfilling	16	kg
Transport distance	50	km
Capacity utilization	50	%

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	MND	MND	MND	MNR	MNR	MNR	MND	MND	MND	X	MND	X	MND

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 m³ GMW 036-037-038 unfaced rolls

Parameter	Unit	A1-A3	A4	C2	C4
Global warming potential	[kg CO ₂ -Eq.]	15.60	0.89	0.05	0.22
Depletion potential of the stratospheric ozone layer	[kg CFC11-Eq.]	1.28E-8	4.26E-12	2.54E-13	2.95E-12
Acidification potential of land and water	[kg SO ₂ -Eq.]	1.50E-1	2.45E-3	1.62E-4	1.38E-3
Eutrophication potential	[kg (PO ₄) ³⁻ -Eq.]	2.62E-2	5.05E-4	3.43E-5	1.89E-4
Formation potential of tropospheric ozone photochemical oxidants	[kg ethene-Eq.]	8.24E-3	-6.30E-4	-4.59E-5	1.29E-4
Abiotic depletion potential for non-fossil resources	[kg Sb-Eq.]	9.60E-4	3.34E-8	2.00E-9	8.12E-8
Abiotic depletion potential for fossil resources	[MJ]	259.00	12.30	0.73	2.85

RESULTS OF THE LCA - RESOURCE USE: 1 m³ GMW 036-037-038 unfaced rolls

Parameter	Unit	A1-A3	A4	C2	C4
Renewable primary energy as energy carrier	[MJ]	38.70	IND	IND	IND
Renewable primary energy resources as material utilization	[MJ]	0.00	IND	IND	IND
Total use of renewable primary energy resources	[MJ]	38.70	0.48	0.03	0.25
Non-renewable primary energy as energy carrier	[MJ]	318.00	IND	IND	IND
Non-renewable primary energy as material utilization	[MJ]	26.70	IND	IND	IND
Total use of non-renewable primary energy resources	[MJ]	345.00	12.30	0.74	2.98
Use of secondary material	[kg]	13.20	IND	IND	IND
Use of renewable secondary fuels	[MJ]	0.00	0.00	0.00	0.00
Use of non-renewable secondary fuels	[MJ]	0.00	0.00	0.00	0.00
Use of net fresh water	[m ³]	1.11E-1	3.41E-4	2.04E-5	-1.14E-2

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

1 m³ GMW 036-037-038 unfaced rolls

Parameter	Unit	A1-A3	A4	C2	C4
Hazardous waste disposed	[kg]	1.69E-2	2.81E-5	1.67E-6	1.34E-4
Non-hazardous waste disposed	[kg]	0.67	0.00	0.00	16.00
Radioactive waste disposed	[kg]	3.38E-2	1.61E-5	9.62E-7	5.21E-5
Components for re-use	[kg]	IND	IND	IND	IND
Materials for recycling	[kg]	IND	IND	IND	IND
Materials for energy recovery	[kg]	IND	IND	IND	IND
Exported electrical energy	[MJ]	IND	IND	IND	IND
Exported thermal energy	[MJ]	IND	IND	IND	IND

INTERPRETATION

ENVIRONMENTAL IMPACT

All impacts categories except the abiotic **ADPe** and **ODP** are dominated by the production (A3). This is due to the consumption of energy (electricity and thermal energy) during the production of glass mineral wool products.

The **Abiotic Depletion Potential elements (ADPe)** are dominated by the raw material consumption.

The **Global Warming Potential (GWP)** is dominated by the production, mostly due to energy consumption (gas and electricity). The raw materials and the transport have some impact. The binder (bio-based) has no overall impact.

The **Ozone Depletion Potential (ODP)** is influenced by raw materials, production and packaging.

The **Acidification Potential (AP)** is dominated by the production due to emissions related to the processes and the energy consumption. Mostly, the impact refers to emissions to air: sulphur dioxide, ammonia and nitrogen oxides.

The **Eutrophication Potential (EP)** is significantly influenced by the production due to emissions from the furnace, curing oven, electricity consumption, and binder production.

The **Potential Ozone Photochemical Oxidants (POCP)** is particularly dominated by the production (emissions in curing oven, electricity consumption). The results from the transport are negative due to the NO emissions; NO counteracts the POCP.

USE OF RESOURCES

The primary energy demand from non-renewable resources is dominated by the production of glass mineral wool products (especially due to the energy consumption) and with little influence of raw materials, binder and packaging. The renewable energy demand is dominated by the binder (bio-based), the production (electricity mix) and the packaging (wood pallets).

References

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.):
Generation of Environmental Product Declarations
(EPDs);

General principles

for the EPD range of Institut Bauen und Umwelt e.V.
(IBU), 2013/04
www.bau-umwelt.de

ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and
declarations — Type III environmental declarations —
Principles and procedures

EN 15804

EN 15804:2012-04+A1 2013: Sustainability of
construction works — Environmental Product
Declarations — Core rules for the product category of
construction products

IBU 2014 Part B

PCR -Part B: Requirements on the EPD for Mineral
insulating materials (in German „Anforderungen an die
EPD für Mineralische Dämmstoffe“), Version 1.3
Institut Bauen und Umwelt e.V., www.bau-umwelt.com,
07/2014

GaBi 6 2012

GaBi 6: Software and database for life cycle
engineering. LBP, University of Stuttgart and PE
INTERNATIONAL AG, Leinfelden-Echterdingen, 2012.

GaBi 6 2012B

GaBi 6: Documentation of GaBi6-Datasets for life cycle
engineering. LBP University of Stuttgart and PE
INTERNATIONAL AG, 2012.
<http://documentation.gabi-software.com/>

SoFi 5.8. 2014

SoFi 5.8 : Database for Enterprise Sustainability
Performance. PE INTERNATIONAL AG, Leinfelden-
Echterdingen, 2014.

DIN 4108-10

DIN 4108-00 (2004-09): Thermal insulation and energy
economy in buildings - Part 10: Application-related
requirements for thermal insulation materials - Factory
made products

EN 13162

EN 13162:2012 Thermal insulation products for
buildings - Factory made mineral wool (MW) products -
Specification

EN 12667

EN 12667: 2001 Thermal performance of building
materials and products - Determination of thermal
resistance by means of guarded hot plate and heat
flow meter methods - Products of high and medium
thermal resistance

EN 1602

EN 1602: 2013 Thermal insulating products for building
applications - Determination of the apparent density

EN 29053

EN 29053: 1993 Acoustics; materials for acoustical
applications; determination of airflow resistance

EN 1609

EN 1609: 2013 Thermal insulating products for building
applications - Determination of short term water
absorption by partial immersion

EN 12087

EN 12087: 2013 Thermal insulating products for
building applications - Determination of long term water
absorption by immersion

EN 13501-1

EN 13501-1: 2009 Fire classification of construction
products and building elements - Part 1: Classification
using test data from reaction to fire tests

ISO 10456

ISO 10456: 2007 Building materials and products -
Hygrothermal properties - Tabulated design values and
procedures for determining declared and design
thermal values

Regulation (EU) No 305/2011/

Regulation (EU) No 305/2011/ laying down
harmonised conditions for the marketing of
construction products and repealing Council Directive
89/106/EEC .

Regulation (EC) No 765/2008

Regulation (EC) No 765/2008 setting out the
requirements for accreditation and market surveillance
relating to the marketing of products and repealing
Regulation (EEC) No 339/93

Zulassung Z-23. 15-1461

Zulassung Z-23. 15-1461 Building inspection approval
issued by the Deutsches Institut für Bautechnik (DIBt),
Berlin. Wärmedämmstoffe aus Mineralwolle (MW)
nach DIN EN 13162:2009-02.

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@bau-umwelt.com
Web www.bau-umwelt.com

**PE INTERNATIONAL****Author of the Life Cycle Assessment**

PE International
Hauptstrasse 111
70771 Leinfelden-Echterdingen
Germany

Tel +497113418170
Fax +4971134181725
Mail info@pe-international.com
Web www.pe-international.com



Université de Liège
Allée du 6 Aout B6
4000 Sart-Tilman (Liège)
Belgium

Tel +3243663547
Fax +3243664435
Mail saicha.gerbinet@ulg.ac.be
Web www.chimapp.ulg.ac.be

**Owner of the Declaration**

Knauf Insulation
Rue E. Francqui 7
1435 Mont-Saint-Guibert
Belgium

Tel +3210488458
Fax +3210488474
Mail sustainability@knaufinsulation.com
m
Web www.knaufinsulation.com